

Date of issue: 2020.01.06
Valid until: 2023.01.01

Meets the requirements of the Danish Building Regulations 18 (in the following 'BR 18')


APPROVAL HOLDER:

J. Honore Care ApS
Karetmagervej 19 b
DK-7000 Fredericia
Phone: +45 75563244
Internet: www.toilet-bidet.dk

**Documentation of the mechanical/physical properties of
CareBidets model Jasmin 2.0
type jhc-511 og jhc-512**
MAKE:

J. Honore Care ApS, Danmark

MARKING:

- J. Honore Care ApS
- Approval number
- Approval mark: 

QUALITY CONTROL:

The holder of this approval maintains compulsory control agreement with the Danish Technological Institute, Aarhus, Denmark.

This approval only takes into account the requirements of BR 18 to document the mechanical/physical properties, see section 418.

The approval holder is obliged to ensure that the requirements of the Building Regulations section 407 paragraph 3 are met.

CONDITIONS FOR INSTALLATION AND USE:

jhc-511 and jhc-512 can be mounted on toilet bowls with the corresponding dimensions.

Specifications provided by the approval holder.

A shut off valve must be mounted on the water inlet to the toilet seat water tank. The shut of valve may be mounted on water supply line for both the water tank and the toilet.

Detailed mounting- and operating instructions, must follow each toilet seat.

In addition, the installation must be carried out in accordance with DS 439, Standard for Water installations.

Prior to use, the building owner must ensure that section 419 of BR 18 is met.

PLEASE NOTE:

This VA approval only addresses the connection to the water supply network and not to the functions and efficiency of the product.

DESCRIPTION AND TECHNICAL DATA:

Construction	Toilet seat with built-in washing and drying function, for mounting on floor standing and wall-hung toilet bowls. The toilet seat has a built-in electric water heater and tank that supplies the shower device.
Connection	Connection through ½ " RG nipple. The toilet seat has a backflow preventer with built-in air gap according to DS/EN1717, medium category 5, type AB
Function	The electric water heater has an adjustable temperature range of 20-40 °C Built-in adjustable air-drying function. The shower device has automatic cleaning of the rinse arms after use.
Operating pressure	1-10 bar
Electricity	Connection: 230V grounded Power: 0,5 kW