

PRODUCT INSTRUCTION SHEET



REFERENCE 172 Uppingham combined shower & commode chair

172-LONGARMS- Uppingham combined shower & commode chair

(LONG ARMED VERSION)

172WH - Footrest

DESCRIPTION

Manufactured from peel resistant, plastic coated steel tubing, this very robust stylish product is supplied with a comfortable PU Cellular Moulded gap-fronted seat, backrest, over seat and padded hinged armrests. The unit features a pushing handle and 4 braked nylon castors (125mm diameter) and commode bowl. Also included is a rota molded plastic detachable footrest with 2 height positions. The footrest simply clips to the frame and is retracted when not in use. All accessory components are stainless steel for product longevity with re-usability and re-issue in mind.

TECHNICAL SPECIFICATIONS

 Width between arms:
 21" (54cm)

 Seat Height:
 20" (50cm)

 Seat Width:
 17" (42cm)

 Seat Depth:
 17" (42cm)

Aperture Size 11.5" (33cm) x 8.5" (22cm)

Depth of Pot 7"

Height from floor to top of commode seat:

Height from floor to bottom of commode seat:

Overall width:

Overall depth:

Height to top of pushing handle:

Weight limit:

Length of Arms (from back of frame):

20" (51cm)

18" (45.7cm)

25" (64cm)

21" (52cm)

40" (102cm)

160kg (25 Stone)

13" (33cm)

(Long arm version 16" (41cm)



USAGE REQUIREMENTS

- 1. A thorough risk assessment should be carried out when prescribing this product.
- 2. Check all castors are securely fitted before, during and after use.
- 3. Ensure the spindle bolt which holds the lift up arms is tightened at all times.
- 4. The chair is designed to be used on level surfaces only.
- 5. If using a moulded footrest make sure the sides are properly located on the bottom struts of the frame, and move freely from front to rear and vice versa.
- 6. The footrest has 2 height positions; the higher position must be used for children or smaller adults only to prevent tipping off the unit when in use.
- 7. When in use we advise that all 4 brake castors are secured at all times and the first 2 castors have the brake pedal facing the front, and parallel with the side of the chair. This will prevent the chair from tipping if the client leans forward.
- 8. The chair is designed to withstand temperatures provided by the latest disinfecting commercial washing machines. Otherwise, use a soft cloth dipped in neutral detergent and warm water. Do not use harsh abrasive materials. To disinfect, clean as above and wipe over with a solution of one thousand parts per million chloride disinfectant-rinse and dry.
- 9. This product is intended for use in a wet room / shower. It is not intended for use outside and should not be immersed in water for long periods of time. Ensure the product is dried thoroughly after use.